R&S®ESSENTIALS

TODAY'S SOLUTION FOR TOMORROW'S CHALLENGE

Save up to 49% on the most popular T&M instrument configurations



www.rohde-schwarz.com/us/complete-promotion

UP 49% OFF R&S®ESSENTIALS

Order before March 31, 2025



Make ideas real



PROMOTIONAL OFFER AT A GLANCE

Save up to 49% on the most popular configurations of T&M instrument configurations from Rohde & Schwarz. This promotional offer includes all essential instruments found on an engineer's workbench: oscilloscopes, DC power supplies, spectrum and antenna analyzers, signal generators, LCR meters and source measure units (SMU).

Rohde & Schwarz has carefully chosen the optimal configurations so that our customers will not need to invest in future upgrades to meet tomorrow's test and measurement challenges. We offer:

- ► Options included upfront at point of purchase
- ► No configuration necessary we take care of it
- ► Single price for each instrument, no upgrades needed
- ► Maximum bench performance and maximum savings

Offer valid until March 31, 2025

Oscilloscopes up to 49 % off

- ▶ Up to 2 GHz bandwidth
- ► Up to 4.5 million waveforms/s real-time update rate
- ▶ Up to 5 Gsample/s sample rate
- ► 400 Mpoints (MXO 4), 500 Mpoints (MXO 5) per channel standard memory
- ▶ 12-bit ADC at all sample rates

DC power supplies up to 19% off

- ▶ Up to 4 channels
- ► Up to 800 W maximum output power
- ► Electrically equivalent channels
- ► Max. voltage: 2 × 100 V/channel
- ► Max. current: 4 × 10 A/channel or 40 A in total

Spectrum analyzers up to 40 % off

- ► Frequency range: 5 kHz to 26.5 GHz
- ► DANL: typ. –163 dBm
- ► Phase noise: typ. –108 dBc (1 Hz)
- ► Intuitive operation
- ► Small test bench footprint







Source measure unit 14% off

- ➤ Two quadrants: operate as source and sink
- ► High-speed data acquisition
- Voltage priority and current priority mode
- ► High-capacitance mode
- ► Fast load regulation
- ► Battery simulation

Vector signal generator 13% off

- ► Frequency range: 8 kHz to 3 GHz
- ► Max. output level of typ. > +25 dBm
- ► Full software option defined vector signal generator with 5" touchscreen
- ► Modulation bandwidth up to 240 MHz

LCR meter 10% off

- ► Max. test frequency: up to 10 MHz
- ► Max. bias voltage: up to 40 V
- Sweep and binning measurement functions
- ▶ Basic accuracy of ±0.05%







UP TO 49 % SAVINGS ON THE CONFIGURATIONS

Oscilloscopes

Model	Bandwidth, channels	Product bundle description		Discount
R&S®RTC-BNDL	300 MHz, 2 analog channels	R&S®RTC1002: ARB generator, trigger and decode (I²C/SPI/UART/RS-232/CAN/LIN) \$1		34%
R&S®RTB-BNDL	300 MHz, 4 analog channels	$R\&S^*RTB2004: ARB\ generator,\ trigger\ and\ decode\ (I^2C/SPI/UART/RS-232/CAN/LIN),\ history\ and\ segment\ memory,\ frequency\ response\ analysis\ (Bode\ plot)$	\$7,170 \$4,145	42%
R&S®RTM-BNDL	1 GHz, 4 analog channels	R&S*RTM3004: ARB generator, trigger and decode (I²C/SPI/UART/RS-232/CAN/LIN/I²S/MIL-STD-1553/ARINC 429), history and segmented memory, power analysis, frequency response analysis (Bode plot), spectrum analysis and spectrogram	\$19,860 \$10,490	47 %
R&S®RTA-BNDL	1 GHz, 4 analog channels	R&S*RTA4004: ARB generator, trigger and decode (I²C/SPI/UART/RS-232/CAN/LIN/I²S/MIL-STD-1553/ ARINC 429), history and segmented memory, power analysis, frequency response analysis (Bode plot), spectrum analysis and spectrogram	\$23,835 \$13,115	45 %
R&S®MX044-BASC	200 MHz, 4 analog channels	MXO 44: ARB generator	\$10,500 \$8,925	15%
R&S®MXO44-PRO	500 MHz, 4 analog channels	MXO 44: low speed serial buses (I ² C/SPI/QuadSPI/UART/RS-232/RS-422/RS-485), automotive protocols (CAN/CAN FD/CAN XL/LIN), automotive Ethernet bus (10BASE-T1S), power analysis, frequency response analysis, MIPI low speed protocols, ARB generator	\$37,470 \$20,985	44 %
R&S®MXO44-ULTM	1.5 GHz, 4 analog channels	MXO 44: low speed serial buses (I²C/SPI/QuadSPI/UART/RS-232/RS-422/RS-485), automotive protocols (CAN/CAN FD/CAN XL/LIN), automotive Ethernet bus (10BASE-T1S), power analysis, frequency response analysis, MIPI low speed protocols, ARB generator, mixed signal option (MSO), memory option 800 Mpoints		49%
R&S®MX054-BASC	350 MHz, 4 analog channels	MXO 54: ARB generator	\$19,130 \$16,995	11%
R&S®MX054-PRO	500 MHz, 4 analog channels	MXO 54: low speed serial buses (I ² C/SPI/QuadSPI/UART/RS-232/RS-422/RS-485), automotive protocols (CAN/CAN FD/CAN XL/LIN), automotive Ethernet buses (10BASE-T1S, 100BASE-T1), power analysis, frequency response analysis, MIPI low speed protocols, ARB generator	\$42,615 \$24,720	42 %
R&S®MX054-ULTM	2 GHz, 4 analog channels	MXO 54: low speed serial buses (I²C/SPI/QuadSPI/UART/RS-232/RS-422/RS-485), automotive protocols (CAN/CAN FD/CAN XL/LIN), automotive Ethernet buses (10BASE-T1S, 100BASE-T1), power analysis, frequency response analysis, MIPI low speed protocols, ARB generator, mixed signal option (MSO), memory option 1 Gpoint	\$ 57,960 \$30,800	47 %
R&S®MX058-BASC	100 MHz, 8 analog channels	MXO 58: ARB generator	\$21,530 \$19,780	8%
R&S®MX058-PRO	500 MHz, 8 analog channels	MXO 58: low speed serial buses (I ² C/SPI/QuadSPI/UART/RS-232/RS-422/RS-485), automotive protocols (CAN/CAN FD/CAN XL/LIN), automotive Ethernet buses (10BASE-T1S, 100BASE-T1), power analysis, MIPI low speed protocols, ARB generator	\$57,035 \$36,565	36 %
R&S®MX058-ULTM	2 GHz, 8 analog channels	MXO 58: low speed serial buses (I²C/SPI/QuadSPI/UART/RS-232/RS-422/RS-485), automotive protocols (CAN/CAN FD/CAN XL/LIN), automotive Ethernet buses (10BASE-T1S, 100BASE-T1), power analysis, frequency response analysis, MIPI low speed protocols, ARB generator, mixed signal option (MSO), memory option 1 Gpoint	\$78,045 \$46,250	41%

DC power supplies

Model	Output channels	Maximum output power	Product bundle description	List price US	Discount
R&S®NGE-COM3B	3	100 W	R&S®NGE103B: Ethernet remote control, digital trigger I/O	\$1,785 \$1,440	19%
R&S®NGM-COM2B	2	120 W	R&S®NGM202: digital trigger I/O, digital voltmeter functionality, battery simulation	\$8,720 \$7,695	12%
R&S®NGP824-COMB	4	800 W	R&S®NGP824: digital trigger I/O, analog input	\$6,955 \$6,235	10%
R&S®NGA142COMB	2	80 W	R&S®NGA142: digital trigger I/O	\$2,230 \$2,015	10%
R&S®HMP4040COM	4	384 W	R&S®HMP4040: dual interface (USB/Ethernet)	\$3,585 \$3,200	11%
R&S®NGL-COM2B	2	120 W	R&S®NGL200: digital trigger I/O, digital voltmeter functionality, battery simulation	\$4,620 \$4.100	11%

Handheld analyzers

Model	Frequency range	Product bundle description		Discount
R&S®FPH-COM1	5 kHz to 3 GHz	$R\&S^{\$}FPH: preamplifier, modulation analysis, power sensor support, channel power meter, pulse measurement with sensor, interference analysis, receiver mode$	\$16,750 \$10,045	40%
R&S®FPH-INH4	5 kHz to 4 GHz	R&S®FPH: preamplifier, interference analysis, maps	\$11,680 \$8,760	25%
R&S®FPH-INH8	5 kHz to 8 GHz	R&S®FPH: preamplifier, interference analysis, maps	\$15,710 \$11,785	25%
R&S®ZPH-COM1	2 MHz to 4 GHz	R&S®ZPH: GPS support, power sensor support, channel power meter, pulse measurements with power sensor	\$ 9,565 \$5,785	40%
R&S®ZPH-COM2	2 MHz to 4 GHz	R&S®ZPH: preamplifier, spectrum analysis, interference analysis, signal strength mapping, modulation analysis, power sensor support, channel power meter, pulse measurements with power sensor	\$ 19,795 \$11,885	40%

Spectrum analyzers

Model	Frequency range	Product bundle description		Discount
R&S®FPC-COM1	5 kHz to 3 GHz	R&S®FPC1000: preamplifier, modulation analysis, receiver mode, advanced measurements	\$7,620 \$4,575	40%
R&S®FPC-COM2	5 kHz to 3 GHz	R&S*FPC1500: preamplifier, modulation analysis, vector network analysis, receiver mode, advanced measurements	\$10,020 \$6,040	40%
R&S®FPL-EMI3	5 kHz to 3 GHz	R&S®FPL1003: additional interfaces, internal generator, RF preamplifier, EMI measurement application	\$23,220 \$18,665	20%
R&S®FPL-EMI7	5 kHz to 7.5 GHz	R&S®FPL1007: additional interfaces, internal generator, RF preamplifier, EMI measurement application	\$29,285 \$21,980	25%
R&S®FPL1007-TG	5 kHz to 7.5 GHz	R&S*FPL1007: OCXO reference frequency, additional interfaces, internal generator, RF preamplifier, 1 dB steps for electronic attenuator	\$29,560 \$22,170	25%
R&S®FPL1007-P1	5 kHz to 7.5 GHz	$R\&S^*FPL1007: \ OCXO \ reference \ frequency, \ additional \ interfaces, \ RF \ preamplifier, \ 1 \ dB \ steps \ for \ electronic \ attenuator$	\$24,400 \$18,285	25%
R&S®FPL1014-P1	5 kHz to 14 GHz	R&S®FPL1014: OCXO reference frequency, additional interfaces, RF preamplifier, 1 dB steps for electronic attenuator	\$40,835 \$30,515	25%
R&S®FPL1026-P1	5 kHz to 26.5 GHz	R&S®FPL1026: OCXO reference frequency, additional interfaces, RF preamplifier, 1 dB steps for electronic attenuator	\$47,320 \$35,545	25%

Source measure unit

Model	Output channel	Maximum voltage/current	Product bundle description	List price US	Discount
R&S®NGU201COM	1	20 V/8 A	R&S®NGU201: digital trigger I/O, digital voltmeter function, battery simulation	\$10,735 \$9,285	14%

Vector signal generator

Model	Frequency range	Product bundle description	List price US	Discount
R&S®SMCV100BP2	4 kHz to 3 GHz	R&S*SMCV100B: AM/FM/φM (via baseband), pulse modulation, custom digital modulation	\$15,585 \$13,570	13%

LCR meter

Model	Maximum frequency	Basic accuracy	Product bundle description	List price US	Discount
R&S®LCX200COM	10 MHz	$\pm 0.05\%$ for impedance measurements; $\pm 0.03^{\circ}$ for phase measurements	R&S®LCX200: advanced analysis option, binning option, extended bias option	\$21,930 \$19,650	10%

Service at Rohde & Schwarz You're in great hands

- ▶ Worldwide
- ► Local and personalized
- Customized and flexible
- ► Uncompromising quality
- ► Long-term dependability

You can find all of these promotional offers at our authorized distributors in your country.

Rohde & Schwarz representative

Rohde & Schwarz

The Rohde & Schwarz technology group is among the trail-blazers when it comes to paving the way for a safer and connected world with its leading solutions in test & measurement, technology systems and networks & cybersecurity. Founded 90 years ago, the group is a reliable partner for industry and government customers around the globe. The independent company is headquartered in Munich, Germany and has an extensive sales and service network with locations in more than 70 countries.

www.rohde-schwarz.com

Sustainable product design

- ► Environmental compatibility and eco-footprint
- ► Energy efficiency and low emissions
- ▶ Longevity and optimized total cost of ownership

Certified Quality Management

Certified Environmental Management

ISO 14001

Rohde & Schwarz training

www.training.rohde-schwarz.com

Rohde & Schwarz customer support

www.rohde-schwarz.com/support



R&S° is a registered trademark of Rohde & Schwarz
Trade names are trademarks of the owners
PD 3608.7280.32 | Version 13.00 | September 2024 (sk)
Today's solution for tomorrow's challenge
Data without tolerance limits is not binding | Subject to change
© 2019 - 2024 Rohde & Schwarz | 81671 Munich, Germany